rtd.calculator

Release 0.1.0

HuCorp

Mar 22, 2022

CONTENTS:

1 Intro **1**

2 Usage **3**

3 `rtd.calculator` **5**

3.1 `rtd.calculator.calculator` 5

3.2 `rtd.calculator.operations` 5

3.3 `rtd.calculator.version` 6

4 Indices and tables **7**

Python Module Index **9**

Index **11**

CHAPTER

ONE

INTRO

Welcome to `rtd.calculator`. How to install using pip:

```
$ pip install rtd.calculator
```

CHAPTER

TWO

USAGE

```
In [1]: from rtd.calculator import operations

In [2]: operations.add(1, 2)
Out[2]: 3

In [3]: operations.subtract(1, 2)
Out[3]: -1

In [4]: operations.multiply(1, 2)
Out[4]: 2
```

Testing reads:

```
In [5]: x = open("pyproject.toml").read()

In [6]: print(x)
[build-system]
requires = ["setuptools>=45", "setuptools_scm[toml]>=6.2"]
build-backend = 'setuptools.build_meta'

[tool.setuptools_scm]
write_to = "rtd/calculator/version.py"

[tool.black]
line-length = 120
```

CHAPTER

THREE

RTD.CALCULATOR

3.1 rtd.calculator.calculator

This module contains the Calculator class.

3.1.1 Classes

Calculator	Calculator class for calculating things.

class rtd.calculator.calculator.**Calculator**

Calculator class for calculating things.

3.2 rtd.calculator.operations

This module contains the functions for the calculator.

3.2.1 Functions

add(a, b)	Addition
multiply(a, b)	Multiplication
subtract(a, b)	Subtraction

rtd.calculator.operations.**add**(*a*, *b*)

Addition

rtd.calculator.operations.**multiply**(*a*, *b*)

Multiplication

rtd.calculator.operations.**subtract**(*a*, *b*)

Subtraction

3.3 rtd.calculator.version

rtd.calculator.version.**version = 0.1.1.dev12+gb7cbcee**

rtd.calculator.version.**version_tuple = [0, 1, 1, 'dev12', 'gb7cbcee']**

CHAPTER

FOUR

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

r

rtd.calculator, 5
rtd.calculator.calculator, 5
rtd.calculator.operations, 5
rtd.calculator.version, 6

INDEX

A

`add()` (*in module rtd.calculator.operations*), 5

C

`Calculator` (*class in rtd.calculator.calculator*), 5

M

`module`
- `rtd.calculator`, 5
- `rtd.calculator.calculator`, 5
- `rtd.calculator.operations`, 5
- `rtd.calculator.version`, 6

`multiply()` (*in module rtd.calculator.operations*), 5

R

`rtd.calculator`
- `module`, 5

`rtd.calculator.calculator`
- `module`, 5

`rtd.calculator.operations`
- `module`, 5

`rtd.calculator.version`
- `module`, 6

S

`subtract()` (*in module rtd.calculator.operations*), 5

V

`version` (*in module rtd.calculator.version*), 6

`version_tuple` (*in module rtd.calculator.version*), 6